

國喬苯乙烯物性規格表 (Specifications of GPPC's SM)

特性 Properties		含量 Contents	測試方法 Test Methods
純度 Purity	(Wt. PCT Min)	99.7	ASTM D-5315-90
比重 Specific Gravity	(25/25 °C)	0.9038-0.9057	ASTM D-891
折射率 Refractive Index	(ND At 25 °C, Min)	1.5435	ASTM D-1218-92
顏色 Color	(APHA, Pt-Co, Max)	10	ASTM D-1209-84
醛含量 Aldehydes	(Wt. ppm As C6H5CHO, Max)	200	ASTM D-2119-87
過氧化物含量 Peroxides	(Wt. ppm As H2O2, Max)	100	ASTM D-2340-82
高分子含量 Polymer	(Wt. ppm, Max)	10	ASTM D-2121-90 (Test Method A)
抑制劑含量 Inhibitor	(Wt. ppm, or As Required)	10 -15	ASTM D-2120-77
硫含量 Sulfur	(Wt. ppm, or As S Max)	5	ASTM D-5453-93
氯含量 Chlorides	(Wt. ppm, or As Cl, Max)	5	ASTM D-4929
黏度 Viscosity	(CPS At 25 °C, Max)	0.75	ASTM D-446-79
含水量 Water	(Wt. ppm Max)	180	ASTM D-1364-90
外觀 Appearance		Clear, No Suspended Matter	View

※ 上表所列數據資料僅供參考用，需更詳細資料請與本公司業務代表聯絡。(These property data are typical values and not intended to serve as product specifications. For more detailed information, please contact your Sales Representatives.)